



PINZE SELEZIONATRICI / HANDLING GRAPPLES

Peso escavatore ton Weight excavator ton	1,2 - 1,8	1,8 - 2,5	2,5 - 4,0	4,0 - 7,5		7,5 - 12,0	
Modello / Model	PF 100	PF 150	PF 200	PF 300	PG 300	PF 450	PG 450
A mm	700	900	1100	1300	1300	1500	1500
B mm	490	600	690	870	870	950	950
C mm	680	750	810	930	930	990	990
D mm	740	840	940	1050	1050	1170	1170
E mm	270	300	330	410	410	460	460
F mm	300	400	500	600	600	700	700
Peso Kg / Weight Kg	88	143	203	346	360	445	487
CAP lt	30	60	100	180	140	290	220
Forza max in punta Force max on top	1300	1900	2400	2900	2900	3200	3200
Cilindro azionamento chele / Hydraulic cylinder details							
Press. max bar	180	220	240	275	275	350	350
Portata/Capacity lt/min	6/12	11/23	15/30	20/40	20/40	20/40	20/40
Tempo apertura sec Time opening sec	2,6/1,3	2,8/1,4	2,7/1,4	2,8/1,4	2,8/1,4	2,8/1,4	2,8/1,4
Motore di rotazione / Rotation motor							
Press. max bar	320	320	150	150	150	150	150
Portata/Capacity lt/min	22	22	6/8	9/12	9/12	9/12	9/12
Velocità rotaz. giri/min Rotation speed giri/mini	18	18	15/20	15/20	15/20	15/20	15/20