



NB: AT THE TIME OF ORDER, PLEASE NOTIFY THE VOLTAGE OF THE ELECTRICAL SYSTEM (12-24 V)

THE PL H PIN LOCK HYDRAULIC VERSION ENABLES THE LOCKING AND UNLOCKING OF THE TOOLS WITH FIXED COUPLING SYSTEM. THE LOCKING IS MADE DIRECTLY ON THE BUCKET OR TOOL'S PINS. IN THE MECHANICAL VERSION THE LOCKING AND UNLOCKING STEPS ARE MANUALLY OPERATED BY USING A SPECIAL SPANNER. IN THE HYDRAULIC VERSION THE TOOLS' CHANGING OPERATIONS CAN BE MANAGED DIRECTLY FROM THE CAB. HYDRAULIC **DOUBLE ACTION** CYLINDER WITH BLOCK VALVE.

MECHANIC	TONS (LB)	0,6 - 1,2 (1323 - 2646)		1,2 - 2,5 (2646 - 5512)		2,5 - 4,0 (5512 - 8819)		4,0 - 7,5 (8819 - 16535)		7,5 - 10,0 (16535 - 22046)	
	MOD.	PL10		PL20		PL40		PL60		PL80	
	A MM (IN)	190 (7,5)	225 (9)	255 (10)	360 (14)	425 (17)					
	B MM (IN)	200 (8)	220 (9)	260 (10)	290 (11)	315 (12)					
	C MM (IN)	115 (4,5)	120 (4,7)	130 (5,1)	160 (6,3)	180 (7,1)					
W/O COUPLER	KG (LB)	12 (26)	15 (33)	20 (44)	52 (115)	66 (146)					

HYDRAULIC DOUBLE ACTION	TONS (LB)	2,5 - 4,0 (5512 - 8819)		4,0 - 7,5 (8819 - 16535)		7,5 - 10,0 (16535 - 22046)		10,0 - 14,0 (22046 - 30865)	
	MOD.	PL40 D.E.		PL60 D.E.		PL80 D.E.		PL100 D.E.	
	A MM (IN)	255 (10)	360 (14)	425 (17)	480 (19)				
	B MM (IN)	260 (10)	290 (11)	315 (12)	400 (16)				
	C MM (IN)	130 (5,1)	160 (6,3)	180 (7,1)	220 (9)				
W/O COUPLER	KG (LB)	30 (66)	55 (121)	68 (150)	125 (276)				
MAX	bar (psi)	200 (2901)	200 (2901)	200 (2901)	200 (2901)				



OPTIONAL

- 1 HYDRAULIC INSTALLATION KIT**
WITH THE HYDRAULIC QUICK COUPLER THE INSTALLATION KIT CAN BE PROVIDED, INCLUDING SOLENOID VALVE AND ELECTRIC SWITCH WITH MAGNETS TO EASILY PUT IT INSIDE THE CAB
- 2 LIFTING HOOK**
A HOOK APPROVED FOR LIFTING OPERATIONS CAN BE WELDED DIRECTLY ON THE QUICK COUPLER.
- 3 INTERFACE**
- 4 SET OF PINS**