


- PATENTED
- APPROVED SWISS MARKET
- HB400



NB: AT THE TIME OF ORDER, PLEASE NOTIFY THE VOLTAGE OF THE ELECTRICAL SYSTEM (12-24 V)

THE **REVERSIBLE** CM SICURMATIC QUICK COUPLER IS EQUIPPED WITH THE MOST ADVANCED SAFETY SYSTEMS: THE FRONT SAFETY SYSTEM THAT IS ACTIVATED WHEN THE PINS COME OUT; THE FORK WITH ITS NEW DOUBLE-NOTCH PROFILE; THE VISUAL INDICATOR THAT SHOWS THE OPERATOR THE LOCKING STATUS FROM THE CAB. SIDES ARE MADE IN HB400. THANKS TO ITS SEMI-AUTOMATIC SYSTEM, THE MECHANICAL VERSION REQUIRES THE OPERATOR'S INTERVENTION ONLY DURING THE UNLOCKING PHASE, WHILE THE LOCKING FUNCTION IS AUTOMATIC. WITH ITS **DOUBLE ACTION** SYSTEM, THE HYDRAULIC VERSION ALLOWS TO MANAGE BOTH THE LOCKING AND UNLOCKING OPERATIONS DIRECTLY FROM THE CAB IN A FEW SECONDS.

MECHANIC SEMI-AUTOMATIC		TONS (LB)	0,6 - 1,8 (1323 - 3968)	1,5 - 2,5 (3307 - 5512)	2,5 - 4,0 (5512 - 8818)	4,0 - 7,5 (8818 - 16535)	7,5 - 10,0 (16535 - 22046)
MOD.		CM20 S.A.	CM30 S.A.	CM30 S.A.	CM100 S.A.	CM100 S.A.	
	A MM (IN)	158 (6,2)	180 (7,1)	180 (7,1)	228 (9)	228 (9)	
	B MM (IN)	170 (6,7)	180 (7,1)	180 (7,1)	292 (11,5)	292 (11,5)	
	C MM (IN)	93 (3,6)	112 (4,4)	112 (4,4)	149 (5,9)	149 (5,9)	
	Ø MM (IN)	30 (1,2)	35 (1,3)	35 (1,3)	50 (1,9)	50 (1,9)	
	KG (LB)	12 (27)	16 (35)	16 (35)	45 (99)	45 (99)	

STANDARD TECHNICAL FEATURES

- FORK'S DOUBLE PROFILE**
NEW DOUBLE CRADLE PROFILE CREATE A GREATER OBSTACLE TO THE ACCIDENTAL FALL OF THE TOOL.
- VISUAL MARKER OF THE COUPLING CONDITION**
THANKS TO THE VISUAL MARKER ON THE COUPLER, THE DISPLAY OF THE COUPLING CONDITION IS EASY AND IMMEDIATE:
A LOCKED PINS **B** UNLOCKED PINS

OPTIONAL

- LIFTING HOOK**
A HOOK APPROVED FOR LIFTING OPERATIONS CAN BE WELDED DIRECTLY ON THE QUICK COUPLER.
- CM ADAPTER**
THE ADAPTER APPLIED TO ANY TOOL ENABLES THE COUPLING WITH THE CM QUICK COUPLER.

