



NB: AT THE TIME OF ORDER, PLEASE NOTIFY THE VOLTAGE OF THE ELECTRICAL SYSTEM (12-24 V)

THE CR TWIN LOCK PATENTED **REVERSIBLE** QUICK COUPLER ENABLES THE FAST LOCKING AND UNLOCKING OF THE ATTACHMENT TOOLS CONSIDERABLY REDUCING THE TIME FOR THEIR REPLACEMENT. THE MECHANICAL VERSION IS PROVIDED WITH A SEMI-AUTOMATIC SYSTEM THAT REQUIRES THE MANUAL INTERVENTION WHEN THE TOOL HAS TO BE RELEASED. BOTH THE LOCKING AND THE SAFE BLOCKING OF THE NEW TOOL ARE AUTOMATIC OPERATIONS. IN THE HYDRAULIC VERSION ALL THESE FUNCTIONS ARE MANAGED DIRECTLY FROM THE CAB.

	TONS (LB)	0,6 - 1,8 (1323 - 3968)	1,8 - 2,5 (3968 - 5512)	2,5 - 4,0 (5512 - 8819)	4,0 - 6,0 (8819 - 13228)	6,0 - 12,0 (13228 - 26455)
	MOD.	CR15	CR30	CR40	CR50	CR70
A	MM (IN)	247 (9,7)	252 (9,9)	260 (10,2)	290 (11,4)	345 (13,5)
B	MM (IN)	156 (6,1)	180 (7,1)	196 (7,7)	218 (8,6)	257 (10,1)
C	MM (IN)	101 (4,0)	107 (4,2)	109 (4,3)	133 (5,2)	148 (5,8)
Ø	MM (IN)	40 (1,6)	45 (1,8)	45 (1,8)	50 (2,0)	60 (2,4)

MECHANIC SEMI-AUTOMATIC		MOD.	CR15 S.A.	CR30 S.A.	CR40 S.A.	CR50 S.A.	CR70 S.A.
	W/O COUPLER	KG (LB)	20 (44)	25 (55)	28 (62)	39 (86)	62 (137)

HYDRAULIC SINGLE ACTION		MOD.	CR15 S.E.	CR30 S.E.	CR40 S.E.	CR50 S.E.	CR70 S.E.
	W/O COUPLER	KG (LB)	21 (46)	27 (60)	29 (64)	40 (88)	63 (139)
	MAX	BAR (PSI)	250 (3626)	250 (3626)	250 (3626)	250 (3626)	200 (2901)



STANDARD TECHNICAL FEATURES

- 1 "SAFE CHECK" SIDE COUPLING INDICATOR**
THE 'SAFE CHECK' SIDE INDICATOR ALLOWS THE QUICK COUPLER'S FULL CONTROL OVER THE ADAPTER. IT PERMITS TO CHECK IF THE QUICK COUPLER IS IN THE RIGHT POSITION TO ENSURE CORRECT COUPLING ONCE THE PINS ARE OUT.

OPTIONAL

- 2 HYDRAULIC INSTALLATION KIT**
WITH THE HYDRAULIC QUICK COUPLER THE INSTALLATION KIT CAN BE PROVIDED, INCLUDING SOLENOID VALVE AND ELECTRIC SWITCH WITH MAGNETS TO EASILY PUT IT INSIDE THE CAB
- 3 LIFTING HOOK**
A HOOK APPROVED FOR LIFTING OPERATIONS CAN BE WELDED DIRECTLY ON THE QUICK COUPLER.
- 4 CR ADAPTE**
THE CR ADAPTER MAKES THE TOOL REVERSIBLE.