


V SCREENING BUCKET




PATENTED

HB400



NB: AT THE TIME OF ORDER, PLEASE NOTIFY THE VOLTAGE OF THE ELECTRICAL SYSTEM (12-24 V)

IDEAL BOTH FOR THE GRADING OF BULK MATERIALS FROM DEMOLITION OR DIGGING WORKS AND THE MIXING OF TERRAIN AND PEAT. THE SCREENING OPERATION IS CARRIED OUT BY AN HYDRAULIC SIEVE WITH ROTATING HB400 KNIVES. THE MATERIAL THICKNESS CAN VARY FROM 0 TO 20 MM (0 - 0,8 IN) AND 0 TO 35 MM (0 - 1,4 IN) WITH A STANDARD EQUIPMENT. CUSTOMIZED SHAFTS CAN ALSO BE SUPPLIED.



W/O COUPLER

W/ COUPLER

W/ COUPLER

W/ COUPLER

W/ COUPLER

W/ COUPLER

TONS (LB)	3,0 - 5,0 (6614 - 11023)	5,0 - 7,5 (11023 - 16535)	7,5 - 10,0 (16535 - 22046)	10,0 - 14,0 (22046 - 30865)
MOD.	V400	V600	V1000	V1200
A MM (IN)	900 (35)	900 (35)	1000 (39)	1200 (47)
B MM (IN)	800 (31)	940 (37)	1050 (41)	1100 (43)
C MM (IN)	660 (26)	795 (31)	930 (37)	1070 (42)
D MM (IN)	570 (23)	710 (28)	850 (34)	990 (39)
KG (LB)	240 (529)	310 (683)	520 (1146)	750 (1653)
KG (LB)	430 (948)	600 (1323)	1000 (2205)	1410 (3108)
MM (IN)	0/20-0/35 (0/0,8-0/1,4)	0/20-0/35 (0/0,8-0/1,4)	0/20-0/35 (0/0,8-0/1,4)	0/20-0/35 (0/0,8-0/1,4)
MIN. - MAX.	L/MIN (GAL/MIN)	40/70 (11/19)	40/70 (11/19)	60/90 (16/24)
	N.	2	3	3
	L (GAL)	125 (33)	195 (51,5)	320 (84,5)
				440 (116,2)

	V400	V600	V1000	V1200
N.	4	4	5	6
4 DC TEETH	DC 3 (KG 2,1)	DC 3 (KG 2,1)	DC 6 (KG 4,0)	DC 6 (KG 4,0)
4 DTE TEETH	DTE 13 (KG 1,7)	DTE 17 (KG 3,0)	DTE 17 (KG 3,0)	DTE 17 (KG 3,0)

NB: ADAPTERS NOT INCLUDED: THE MACHINE CONNECTION PLATE IS INCLUDED FOR ALL THE ADAPTERS IN CANGINI CATALOGUE EXCEPT FOR MOD. ADAPTERS CS 100, CS 100 JANUS, CW 20S, CW30S.



STANDARD

1 SAFETY VALVE

IT PROTECTS THE ENGINE AGAINST THE PRESSURE PEAKS OCCURRING DURING THE WORKING CYCLES.

2 SHAFT SYSTEM

ALL KNIVES ARE MADE OF HB400. DIFFERENT SHAFT CONFIGURATIONS REALIZED UPON REQUEST.

3 PATENTED SHAFT REPLACEMENT SYSTEM

THANKS TO THE PATENTED SYSTEM, IT IS POSSIBLE TO REPLACE SHAFTS RAPIDLY AND MODIFY THE SIEVED MATERIAL SIZE, WITHOUT INTERVENING ON TRANSMISSION.

OPTIONAL

4 DC TEETH DTE TEETH

5 FLOW-REVERSAL VALVE KIT

THIS VALVE ENABLES TO MAKE THE HYDRAULIC FLOW BI-DIRECTIONAL AND USE THE SCREENING BUCKET EVEN WITH MACHINES HAVING A MONO-DIRECTIONAL SYSTEM.

6 FLOWRATE REDUCERS

FLOWRATE REDUCERS. ADVISED FOR MACHINES WITH OILFLOW HIGHER THAN 70 L/MIN.