



RCB SINGLE-FORCE RIPPER & RN MULTI-FORCE RIPPER



HB400



SINGLE-FORCE RIPPER IS MANUFACTURED ENTIRELY IN HB400. SUITABLE FOR SOIL TILTING, DIGGING, ROOT AND STONE GRUBBING WORKS.

	TONS	0,6 - 2,5 (1323 - 5512)		2,5 - 4,0 (5512 - 8818)		4,0 - 7,5 (8818 - 16535)		7,5 - 14,0 (16535 - 30865)	
	MOD.	RCB45		RCB53		RCB67		RCB80	
	A	MM (IN)	250 (10)	265 (10)	295 (12)	340 (13)			
	B	MM (IN)	490 (19)	530 (20)	665 (26)	790 (31)			
	C	MM (IN)	450 (18)	520 (20)	660 (26)	820 (32)			
	W/O COUPLER	KG (LB)	23 (50)	32 (70)	60 (132)	100 (220)			
	DC TEETH		DC 3 KG 2,1	DC 6 KG 4,0	DC 8 KG 5,4	DC 13 KG 13			
	DTE TEETH		DTE 13 KG 1,7	DTE 17 KG 3,0	DTE 17 KG 3,0	DTE 23 KG 8,8			

MULTI-FORCE RIPPER IS PARTICULARLY SUITABLE FOR SOIL TILLING AND ROOT OR STONE GRABBING WORKS. ENTIRELY REALIZED IN HB400.

	TONS	1,2 - 2,5 (2646 - 5512)		2,5 - 4,0 (5512 - 8818)		4,0 - 7,5 (8818 - 16535)		7,5 - 14,0 (16535 - 30865)		
	MOD.	RN30	RN30	RN40	RN40	RN50	RN50	RN70	RN70	
	A	MM (IN)	400 (16)	600 (24)	500 (20)	800 (31)	600 (24)	1000 (39)	800 (31)	1200 (47)
	B	MM (IN)	300 (12)	300 (12)	320 (14)	320 (14)	380 (15)	380 (15)	507 (20)	507 (20)
	C	MM (IN)	400 (16)	400 (16)	465 (18)	465 (18)	555 (22)	555 (22)	710 (28)	710 (28)
		KG (LB)	27 (60)	33 (72)	35 (77)	46 (101)	64 (141)	83 (182)	137 (302)	170 (374)
		N.	3	4	3	4	4	5	5	6
	DC TEETH		DC 1 (KG 1,4)	DC 1 (KG 1,4)	DC 1 (KG 1,4)	DC 1 (KG 1,4)	DC 3 (KG 2,1)	DC 3 (KG 2,1)	DC 6 (KG 4,0)	DC 6 (KG 4,0)
	DTE TEETH		DTE 13 (KG 1,7)	DTE 13 (KG 1,7)	DTE 13 (KG 1,7)	DTE 13 (KG 1,7)	DTE 17 (KG 3,0)	DTE 17 (KG 3,0)	DTE 17 (KG 3,0)	DTE 17 (KG 3,0)



STANDARD TECHNICAL FEATURES

- 1 DC TEETH DTE TEETH